



RAC10 Small SpaceCooling®


Intelligent heat removal and monitoring solution for servers, network switches and phone systems in small spaces.

The RAC10 system evacuates heat load from the small space and sends it to the outside corridor or ceiling plenum return. Maintain a perfectly controlled environment for your small computer and network rooms using building air while providing the needed visibility to cooling capacity and environment information and alarms. Email alerts and the web interface provides remote alarms and management for superior visibility and control of room environment.


Features:

- Fully redundant room heat exhaust based on a set flow rate or temp control.
- Continually deliver cool air to your IT equipment.
- Real-time plus historical cooling capacity and environment monitoring.
- Early alarm notification to email account/s through a secure Ethernet connection. Allow multiple email or SNMP trap recipients with escalation
- Quickly deploy into ceiling or attach to wall in minutes. Web browse to device, set-up email and/or communicate with existing management software.

Wall Mount



Ceiling Mount



RAC10 System

Wall or ceiling mount for automated heat exhaust and critical monitoring / alerts. Optional SC System for room air supply required for some room and load conditions.

Specifications

Input: 120 VAC, 50/60 Hz, 10FT Cord, NEMA 5-15P

Fan Speed Regulation: Automatic temperature control with Ethernet remote adjustment

Airflow:
1100 CFM Maximum

Environmental Monitoring: Ethernet remote access and alarms, up to four RJ12 Temperature sensors with 20 FT cords (two included)


Regulation: Temperature based, range: 60 to 120F

Physical: 23.75 L x 14.00 W x 3.52 H

Network: HTTP / HTTPS / SNMP / DHCP

Regulatory: UL, cUL 507, FCC Part 15 Class A

Warranty:
2 Years





Thermal Control & Monitoring Software

- Sensors
- Alarms
- Logging
- Display
- Config
- Control
- Help

PDA/Phone | XML | MIB

Display

General

Default Language: English

Date Format: USA (MM/DD/YY)

Temperature Unit: Celsius

Interface Type: Default

Devices

Unique Address	Device Type	Friendly Name
288F71F500000080	vsfc	<input type="text" value="RFC"/>

Remove all unplugged devices

- Sensors
- Alarms
- Logging
- Display
- Config
- Control
- Help

PDA/Phone | XML | MIB

Alarms

RFC **ID 288F71F500000080**

<p>Internal Temp (F)</p> <p>trips if: Above</p> <p>threshold: <input type="text" value="82.0"/></p>	<p>Alarm must remain tripped for 0 min before notification</p> <p>Repeat every: No Repeat</p>	<p>E-mail: <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p>Traps: <input type="checkbox"/> <input type="checkbox"/></p> <p>Buzzer: <input checked="" type="checkbox"/></p> <p style="text-align: center; color: green; font-weight: bold;">Untripped</p>
<p>Fan Speed</p> <p>trips if: Below</p> <p>threshold: <input type="text" value="25.0"/></p>	<p>Alarm must remain tripped for 0 min before notification</p> <p>Repeat every: No Repeat</p>	<p>E-mail: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p>Traps: <input checked="" type="checkbox"/> <input type="checkbox"/></p> <p>Buzzer: <input type="checkbox"/></p> <p style="text-align: center; color: green; font-weight: bold;">Untripped</p>
<p>Ext. Temp 1 (F)</p> <p>trips if: Above</p> <p>threshold: <input type="text" value="75.0"/></p>	<p>Alarm must remain tripped for 0 min before notification</p> <p>Repeat every: No Repeat</p>	<p>E-mail: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p>Traps: <input type="checkbox"/> <input type="checkbox"/></p> <p>Buzzer: <input checked="" type="checkbox"/></p> <p style="text-align: center; color: red; font-weight: bold;">Tripped</p>

RAC10 Small Space Cooling Intelligent Heat Removal for Computer and Network Systems in Small Spaces	
RAC10-01	0-10 kW Variable FLOW Small Space Cooling & Software Suite 120V Input
RT-20	Temperature Sensor, 20 Foot Cords, 2 Included with RAC-10 System
SC-D002	Duct Discharge Cap

10000801

Geist Americas

800.432.3219
geistglobal.com

Geist DCIM
1.877.449.4150
geistglobal.com

Geist Europe

+44 (0) 1823 275100
geistglobal.com

Geist Asia

China
+86.755.86639505
geistglobal.com

Hong Kong
+852 90361927
geistglobal.com