



## Smoke Alarm

Part Number: SA9120F (120V)  
SA9220F (220V)

## Photoelectric Smoke Alarm

- Detect smoke in your server room

Photoelectric Smoke Alarm for 120VAC/9VDC and 220VAC/9VDC Single or Multiple (Tandem) Station and Specialty Applications

120VAC and 220VAC photoelectric smoke alarm/detector with 9VDC battery back-up as an auxiliary power source in the event of an electrical failure. Features a warning signal for low or missing battery, and a dry-contact relay output suitable for use with any Geist Climate Monitor with analog inputs.

- 120VAC and 220VAC with 9VDC battery back-up
- Low or missing battery indicator
- 9VDC alkaline battery included
- Patented three-position test switch
- Includes 90db piezo solid state non-latching horn
- Tandem connection up to 12 units; 6 on relay models
- Nominal 3.0% sensitivity
- 5:1 signal-to-noise ratio
- Pulsing LED sensing chamber
- Fully insect-screened
- Solid State LED condition indicator
- Quick-disconnect wiring harness
- Mounting hardware adapts to standard junction boxes
- Protective high air velocity gasket
- On-site maintenance washing program (EasyWash™)
- Compliant with NFPA Standards
- Temporal 3 Evacuation Sounding Device (9123 and 9223)



Please note the information contained herein is for informational purposes only. Technical claims listed depend on a series of technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Geist reserves the right to modify these specifications without prior notice. Geist makes no warranties, express or implied, on the information contained in this document.

10009601

### Geist Americas

800.432.3219  
geistglobal.com

Geist DCiM  
1.877.449.4150  
geistglobal.com

### Geist Europe

+44 (0) 1823 275100  
geistglobal.com

### Geist Asia

China  
+86.755.86639505  
geistglobal.com

Hong Kong  
+852 90361927  
geistglobal.com