



Part Number: ENV-DIT



## Description

ENV-DIT - RS-Wi Digital temperature measurement and dry contact (NO/NC) input sensor. Battery operated, microprocessor-controlled.

RS-Wi sensors spend most of the time in a low power, "sleep" state. The onboard microprocessor requires power only at predetermined time intervals (set at the factory). Sensors provide an output signal and the information is wirelessly transmitted to a point managing receiver (RS-Wi wireless gateway). This architecture allows the sensors to consume minimal power, resulting in a battery life of up to four years.

## **Features**

## Specifications:

- Power Input: 3.6V battery lithium AA, included
- Battery Life-Lithium AA Battery: Up to 4 years with 10-17 second random transmission interval
- Shelf Life (battery installed): 10 years in quiescent mode
- Transmission-Interval: 10-17 seconds (random)

Frequency: 418MHZ

Range: Up to 100ft. (30.5m)

- Accuracy: +/-.5°C (+/-1.0°F)
- Operating Temperature: -40 to 85° C (-40 to 185°F)
- Storage Temperature: -40 to 85°C (-40 to 185°F)
- Dimensions: 2.5'W x 2.0' H x 1.0'D (63.5mm W x 50.8mm H x 25.4mm D)
- Weight: 1.5 oz (42.52g)
- Mounting: wall mount or free standing for ease of relocation
- Certification: FCC Part 15, Class B, FCC ID: M5ZP6EZ10

## Product Highlights

- Wireless with compact ABS enclosure
- Transmission range of up to 100 feet (182.88m)
- Moisture resistant coating on electronics
- Internal loop antenna
- Easy installation and simple to relocate
- One year warranty

Please note the information contained herein is for informational purposes only. Technical claims listed depend on a series of technical assumptions. Your experience with these products may differ if you operate the products in an environment, which is different from the technical assumptions. Geist reserves the right to modify these specifications without prior notice. Geist makes no warranties, express or implied, on the information contained in this document.

geistglobal.com

Geist Asia