

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: 11027VH

Model Number: VRELN080-103I44TL6

Category: Basic

Sub Category: Standard

Power Configuration: 30A, 208V, 4.9kW

Physical Configuration: 17in / 432mm, Horizontal/Vertical

Product Summary: rPDU, Basic Standard, 30A, 208V, 4.9kW, Horizontal/Vertical, (4) IEC C13, (4) IEC C19, 10ft power cord with L6-30P, Black Powder Coat.

Plug Form:



L6-30P

Receptacle:



IEC C13
(Quantity: 4)



IEC C19
(Quantity: 4)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--------------------|----------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 30A |

| | |
|--|--|
| VA per Input (Load Capacity) | 4.9kW (208V) |
| Frequency | 50/60Hz |
| Over Current Protection | (4) 15A Thermal Breakers |
| Switch | No |
| Power Cable Wire Gauge | 10/3 |
| Power Cable Length | 10ft |
| Plug Type | NEMA L6-30P Twistlock |
| Combined Total Receptacle/Socket Quantity | 8 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 4 |
| - Quantity per Breaker Pair | 2 |
| - Style | Banks of 2 |
| - Maximum Output per Receptacle/Socket | 15A per receptacle bank |
| - Voltage per Receptacle/Socket | 208V |
| Receptacle/Socket Type #2 | IEC C19 |
| - Quantity on Face | 4 |
| - Quantity per Breaker Pair | 2 |
| - Style | Individual |
| - Maximum Output per Receptacle/Socket | 20A |
| - Voltage per Receptacle/Socket | 208V |
| Continuous Operating Temperature Range | 10-45C / 50-113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 17in / 432mm Vertical/Horizontal Rackmount |
| 19in Panel Mount Brackets | Yes |
| SLB-4 Brackets | Yes |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | UL & c-UL Listed Accessory 1950 |
| Chassis Dimensions (LxWxD) | 17.0in x 1.72in x 1.85in |
| Shipped Weight | 7lbs (3.18kg) |