

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: 11038

**Model Number:** VHVBN248-102C13TL21

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 20A, 120/208V WYE, 5.7kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Basic Standard, 20A, 120/208V WYE, 5.7kW, Vertical, (24) IEC C13, 10ft power cord with L21-20P, Black Powder Coat.

### Plug Form:



L21-20P

### Receptacle:



IEC C13  
(Quantity: 24)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |                      |
|------------------------------|----------------------|
| Quantity Of Inputs           | 1                    |
| Voltage                      | 100-120/200-240V WYE |
| Current                      | 20A x 3 Phase WYE    |
| VA per Input (Load Capacity) | 5.7kW (208V)         |
| Frequency                    | 50/60Hz              |

|  |  |
|--|--|
| <b>Over Current Protection</b>                               | None   |
| <b>Switch</b>  | No   |
| <b>Power Cable Wire Gauge</b>                                | 12/5   |
| <b>Power Cable Length</b>                                    | 10ft   |
| <b>Plug Type</b>   | NEMA L21-20P Twistlock                                 |
| <b>Receptacle/Socket Type #1</b>                             | IEC C13  |
| <b>- Quantity on Face</b>                                    | 24   |
| <b>- Quantity per Phase Combination</b>                      | 8  |
| <b>- Style</b>   | Banks of 4   |
| <b>- Maximum Output per Receptacle/Socket</b>                | 15A per receptacle bank                                |
| <b>- Voltage per Receptacle/Socket</b>                       | 208V   |
| <b>Continuous Operating Temperature Range</b>                | 10-45C / 50-113F                                       |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black  |
| <b>Configuration</b>   | 66in / 1683mm Vertical Rackmount                       |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in                                    |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant |
| <b>Product Warranty</b>                                      | 5-year limited warranty                                |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 60950                                 |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 1.72in x 1.61in                              |
| <b>Shipped Weight</b>  | 13lbs (5.9kg)  |