Vertiv[™] PowerIT rPDU



OVERVIEW

Metered surge protected rPDUs deliver reliable power to critical IT equipment within a rack or cabinet and comes equipped with built-in surge protection and a local power meter displaying real-time power metrics.

Benefits

- Ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.
- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides realtime power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



Part #: 11594VH

Model Number: VSSBCN204-102R20TL

Category: Metered
Sub Category: Surge

Power Configuration: 20A, 120V, 1.9kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary: rPDU, Metered Surge, 20A, 120V, 1.9kW, Vertical, (20) NEMA 5-20R, 10ft power cord

with L5-20P, Black Powder Coat.

Monitoring: Power - Local (A, V, W, PF)

Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave

input

Plug Form:

Receptacle:







NEMA 5-20R (Quantity: 20)

Chassis Color Options:



Product Specification and Options

System Features

Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input Monitoring Level 1 Aggregate - Total Unit Monitoring Quantity Of Inputs 1 Voltage 100-120V Current 20A VA per Input (Load Capacity) 1.5kW (120V) Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1-Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Trechnology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plestic Mounting Clips 1-Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5-year limited warranty Cornected Equipment Warranty 5-year limited warranty Cornected Equipment Warranty 5-year limited warranty Cornication (Agency Approvals CLWXD) 66.25in x 1.61in x 1.61in	System Features	
Quantity of Inputs 1 Voltage 100-120V Current 20A VA per Input (Load Capacity) 1.9kW (120V) Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration	Monitoring	Digital RMS Scrolling Power Meter +/- 2% Accuracy with Full
Voltage 100-120V Current 20A VA per Input (Load Capacity) 1.9kW (120V) Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds	Monitoring Level 1	Aggregate - Total Unit Monitoring
Current 20A VA per Input (Load Capacity) 1.9kW (120V) Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(a) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds	Quantity Of Inputs	1
VA per Input (Load Capacity) 1.9kW (120V) Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1 Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61iin	Voltage	100-120V
Frequency 50/60Hz Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.6tiin x 1.6tiin	Current	20A
Over Current Protection 20A Thermal Breaker Switch No Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time - 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5 - year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	VA per Input (Load Capacity)	1.9kW (120V)
Switch No Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Frequency	50/60Hz
Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 340V Response Time < 5 nanoseconds Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66 in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Over Current Protection	20A Thermal Breaker
Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66 in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5 -year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Switch	No
Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage A40V Response Time 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Indicators - LED(s)	1 - Power ON Green LED
Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time 5 nanoseconds Technology Used Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5 years / \$5,000 Certification/Agency Approvals Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Power Cable Wire Gauge	12/3
Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time <5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1- Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LwWxD) 66.25in x 1.61in x 1.61in	Power Cable Length	10ft
- Quantity on Face 20 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1- Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Plug Type	NEMA L5-20P Twistlock
- Style Individual - Rotated - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Receptacle/Socket Type #1	NEMA 5-20R
- Maximum Output per Receptacle/Socket 20V Center to Center Receptacle Spacing 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time <5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	- Quantity on Face	20
Center to Center Receptacle/Socket 2.8 Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Surge Indicator Red LED Yes Continuous Operating Temperature Range Heavy Steel - Powder Coat Finish Black Configuration Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	- Style	Individual - Rotated
Center to Center Receptacle Spacing Joule Rating 720 Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	- Maximum Output per Receptacle/Socket	20A
Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Surge Indicator Red LED Yes Continuous Operating Temperature Range Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5 - year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	- Voltage per Receptacle/Socket	120V
Maximum Clamping Voltage 340V Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Center to Center Receptacle Spacing	2.8
Response Time < 5 nanoseconds Technology Used Super MOVS Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Joule Rating	720
Technology Used Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Maximum Clamping Voltage	340V
Surge Indicator Red LED Yes Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Response Time	< 5 nanoseconds
Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Technology Used	Super MOVS
Heavy Steel - Powder Coat Finish Configuration 66in / 1683mm Vertical Rackmount 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Surge Indicator Red LED	Yes
Configuration 66in / 1683mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 2 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Continuous Operating Temperature Range	10-45C / 50-113F
Plastic Mounting Clips 1 - Bottom; 2 - Top USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Heavy Steel - Powder Coat Finish	Black
Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Configuration	66in / 1683mm Vertical Rackmount
Product Warranty 5-year limited warranty Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Plastic Mounting Clips	1 - Bottom; 2 - Top
Connected Equipment Warranty 5 years / \$5,000 Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Product Warranty	5-year limited warranty
Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 66.25in x 1.61in	Connected Equipment Warranty	5 years / \$5,000
Chassis Dimensions (LxWxD) 66.25in x 1.61in x 1.61in	Certification/Agency Approvals	RoHS Compliant
	Certification/Agency Approvals	UL & c-UL Listed 60950
Shipped Weight 9lbs (4.08kg)	Chassis Dimensions (LxWxD)	66.25in x 1.61in x 1.61in
	Shipped Weight	9lbs (4.08kg)