

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: 15205VH

**Model Number:** VHVBN449-102MB1TL21

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 20A, 120/208V WYE, 5.7kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Basic Standard, 20A, 120/208V WYE, 5.7kW, Vertical, (36) IEC C13, (6) IEC C19, (2) NEMA 5-20R, 10ft power cord with L21-20P, Black Powder Coat.

### Plug Form:



L21-20P

### Receptacle:



IEC C13  
(Quantity: 36)



IEC C19  
(Quantity: 6)



NEMA 5-20R  
(Quantity: 2)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |                      |
|------------------------------|----------------------|
| Quantity Of Inputs           | 1                    |
| Voltage                      | 100-120/200-240V WYE |
| Current                      | 20A x 3 Phase WYE    |
| VA per Input (Load Capacity) | 5.7kW (208V)         |
| Frequency                    | 50/60Hz              |

|   |   |
|---|---|
| Over Current Protection                               | None  |
| Switch  | No  |
| Power Cable Wire Gauge                                | 12/5  |
| Power Cable Length                                    | 10ft  |
| Plug Type   | NEMA L21-20P Twistlock  |
| Combined Total Receptacle/Socket Quantity             | 44  |
| Receptacle/Socket Type #1                             | IEC C13   |
| - Quantity on Face                                    | 36  |
| - Quantity per Phase Combination                      | 12  |
| - Style   | Banks of 6  |
| - Maximum Output per Receptacle/Socket                | 15A per receptacle bank   |
| - Voltage per Receptacle/Socket                       | 208V  |
| Receptacle/Socket Type #2                             | IEC C19   |
| - Quantity on Face                                    | 6   |
| - Quantity per Phase Combination                      | 2   |
| - Style   | Individual  |
| - Maximum Output per Receptacle/Socket                | 20A   |
| - Voltage per Receptacle/Socket                       | 208V  |
| Receptacle/Socket Type #3                             | NEMA 5-20R  |
| - Quantity on Face                                    | 2   |
| - Quantity A Phase Only                               | 2   |
| - Style   | Duplex  |
| - Maximum Output per Receptacle/Socket                | 20A   |
| - Voltage per Receptacle/Socket                       | 120V  |
| Continuous Operating Temperature Range                | 10-45C / 50-113F  |
| Heavy Steel - Powder Coat Finish                      | Black   |
| Configuration   | 66in / 1683mm Vertical Rackmount  |
| 7938 Vertical Mounting Bracket Kit                    | Yes   |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in   |
| Country of Origin                                     | USA, TAA Compliant and Buy American Act COTS Compliant  |
| Product Warranty                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals                        | RoHS Compliant  |
| Certification/Agency Approvals                        | UL & c-UL Listed 60950  |
| Chassis Dimensions (LxWxD)                            | 66.25in x 2.0in x 2.0in   |
| Shipped Weight  | 23lbs (10.43kg)   |