

## OVERVIEW

Metered surge protected rPDUs deliver reliable power to critical IT equipment within a rack or cabinet and comes equipped with built-in surge protection and a local power meter displaying real-time power metrics.

### Benefits

- Ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.
- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.

## Part #: 17364

**Model Number:** VSSBA204-101S15

**Category:** Metered

**Sub Category:** Surge

**Power Configuration:** 15A, 120V, 1.4kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Metered Surge, 15A, 120V, 1.4kW, Vertical, (20) NEMA 5-15R, 10ft power cord with 5-15P, Black Powder Coat.

**Monitoring:** Current - Local

Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

### Plug Form:



5-15P

### Receptacle:



NEMA 5-15R  
(Quantity: 20)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|   |  |
|---|--|
| <b>Monitoring</b>                             | Current - Local  |
|   | Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input |
| <b>Monitoring Level 1</b>                     | Aggregate - Total Unit Monitoring  |
| <b>Quantity Of Inputs</b>                     | 1  |
| <b>Voltage</b>                                | 100-120V   |
| <b>Current</b>                                | 15A  |
| <b>VA per Input (Load Capacity)</b>           | 1.4kW (120V)   |
| <b>Frequency</b>                              | 50/60Hz  |
| <b>Over Current Protection</b>                | 15A Thermal Breaker  |
| <b>Switch</b>                                 | Yes  |
| <b>Indicators - LED(s)</b>                    | 1 - Power ON Green LED   |
| <b>Power Cable Wire Gauge</b>                 | 14/3   |
| <b>Power Cable Length</b>                     | 10ft   |
| <b>Plug Type</b>                              | NEMA 5-15P   |
| <b>Receptacle/Socket Type #1</b>              | NEMA 5-15R   |
| <b>- Quantity on Face</b>                     | 20   |
| <b>- Quantity per Breaker</b>                 | 20   |
| <b>- Style</b>                                | Individual - In-Line   |
| <b>- Maximum Output per Receptacle/Socket</b> | 15A  |
| <b>- Voltage per Receptacle/Socket</b>        | 120V   |
| <b>Center to Center Receptacle Spacing</b>    | 2.8  |
| <b>Joule Rating</b>                           | 720  |
| <b>Maximum Clamping Voltage</b>               | 340V   |
| <b>Response Time</b>                          | < 5 nanoseconds  |
| <b>Technology Used</b>                        | Super MOVs   |
| <b>Surge Indicator Red LED</b>                | Yes  |
| <b>Continuous Operating Temperature Range</b> | 10-45C / 50-113F   |
| <b>Heavy Steel - Powder Coat Finish</b>       | Black  |
| <b>Configuration</b>                          | 66in / 1683mm Vertical Rackmount   |
| <b>Plastic Mounting Clips</b>                 | 1 - Bottom; 2 - Top  |
| <b>Country of Origin</b>                      | USA, TAA Compliant and Buy American Act COTS Compliant                         |
| <b>Product Warranty</b>                       | 5-year limited warranty  |
| <b>Connected Equipment Warranty</b>           | 5 years / \$5,000  |
| <b>Certification/Agency Approvals</b>         | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>         | UL & c-UL Listed 60950   |
| <b>Chassis Dimensions (LxWxD)</b>             | 66.25in x 1.61in x 1.61in  |
| <b>Shipped Weight</b>                         | 9lbs (4.08kg)  |