

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: 28014VH

Model Number: NSVL080-102S20TL

Category: Basic

Sub Category: Standard

Power Configuration: 20A, 120V, 1.9kW

Physical Configuration: 17in / 432mm, Horizontal/Vertical

Product Summary: rPDU, Basic Standard, 20A, 120V, 1.9kW, Horizontal/Vertical, (8) NEMA 5-20R, 10ft

power cord with L5-20P, Black Powder Coat.

Plug Form: Receptacle:







NEMA 5-20R (Quantity: 8)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	100-120V
Current	20A
VA per Input (Load Capacity)	1.9kW (120V)

Over Current Protection 20A Thermal Breaker Switch Yes Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in		
Switch Yes Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty fregistered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in	Frequency	50/60Hz
Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Over Current Protection	20A Thermal Breaker
Power Cable Wire Gauge 12/3 Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (LwWxD) 17.00in x 1.61in x 1.61in	Switch	Yes
Power Cable Length 10ft Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (LxWxD) 17.00 in x 1.61 in x 1.61 in	Indicators - LED(s)	1 - Power ON Green LED
Plug Type NEMA L5-20P Twistlock Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Power Cable Wire Gauge	12/3
Receptacle/Socket Type #1 NEMA 5-20R - Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in	Power Cable Length	10ft
- Quantity on Face 8 - Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V - Center to Center Receptacle Spacing 1.25 - Continuous Operating Temperature Range 10-45C / 50-113F - Heavy Steel - Powder Coat Finish Black - Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes - Plastic Mounting Clips 1 - Bottom; 1 - Top - Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years - Certification/Agency Approvals UL & c-UL Listed 60950 - Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Plug Type	NEMA L5-20P Twistlock
- Quantity per Breaker 8 - Style Individual - In-Line - Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V - Center to Center Receptacle Spacing 1.25 - Continuous Operating Temperature Range 10-45C / 50-113F - Heavy Steel - Powder Coat Finish Black - Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes - Plastic Mounting Clips 1 - Bottom; 1 - Top - Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years - Certification/Agency Approvals UL & c-UL Listed 60950 - Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Receptacle/Socket Type #1	NEMA 5-20R
-Style Individual - In-Line -Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1- Bottom; 1- Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	- Quantity on Face	8
-Maximum Output per Receptacle/Socket 20A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	- Quantity per Breaker	8
Continuous Operating Temperature Range 10-45C / 50-113F Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	- Style	Individual - In-Line
Center to Center Receptacle Spacing 1.25 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	- Maximum Output per Receptacle/Socket	20A
Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	- Voltage per Receptacle/Socket	120V
Heavy Steel - Powder Coat Finish Configuration 17in / 432mm Vertical/Horizontal Rackmount 19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Center to Center Receptacle Spacing	1.25
Configuration 17in / 432mm Vertical/Horizontal Rackmount Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Continuous Operating Temperature Range	10-45C / 50-113F
19in Panel Mount Brackets Yes Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Heavy Steel - Powder Coat Finish	Black
Plastic Mounting Clips 1 - Bottom; 1 - Top USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Configuration	17in / 432mm Vertical/Horizontal Rackmount
Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	19in Panel Mount Brackets	Yes
Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Plastic Mounting Clips	1 - Bottom; 1 - Top
purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Product Warranty	
Chassis Dimensions (LxWxD) 17.00in x 1.61in x 1.61in	Certification/Agency Approvals	RoHS Compliant
	Certification/Agency Approvals	UL & c-UL Listed 60950
Shipped Weight 4lbs (1.81kg)	Chassis Dimensions (LxWxD)	17.00in x 1.61in x 1.61in
	Shipped Weight	4lbs (1.81kg)