

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard five-year limited warranty.



Part #: 28048VH

Model Number: NSVK080-101R15

Category: Basic

Sub Category: Standard

Power Configuration: 15A, 120V, 1.4kW

Physical Configuration: 24in / 610mm, Vertical

Product Summary: rPDU, Basic Standard, 15A, 120V, 1.4kW, Vertical, (8) NEMA 5-15R, 10ft power cord with

5-15P, Black Powder Coat.

Plug Form:





Receptacle:

(Quantity: 8)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	100-120V
Current	15A
VA per Input (Load Capacity)	1.4kW (120V)
Frequency	50/60Hz

Switch Yes Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in		
Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Certification/Agency Approvals Chassis Dimensions (LxWxD) 24.00in x 1.61in	Over Current Protection	15A Thermal Breaker
Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Switch	Yes
Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Indicators - LED(s)	1 - Power ON Green LED
Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Power Cable Wire Gauge	14/3
Receptacle/Socket Type #1 - Quantity on Face - Style Individual - Rotated - Maximum Output per Receptacle/Socket - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Power Cable Length	10ft
- Quantity on Face 8 - Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1- Bottom; 1- Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Plug Type	NEMA 5-15P
- Style Individual - Rotated - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Receptacle/Socket Type #1	NEMA 5-15R
- Maximum Output per Receptacle/Socket - Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	- Quantity on Face	8
- Voltage per Receptacle/Socket 120V Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	- Style	Individual - Rotated
Center to Center Receptacle Spacing 2.0 Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	- Maximum Output per Receptacle/Socket	15A
Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	- Voltage per Receptacle/Socket	120V
Heavy Steel - Powder Coat Finish Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Center to Center Receptacle Spacing	2.0
Configuration 24in / 600mm Vertical Rackmount Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Continuous Operating Temperature Range	10-45C / 50-113F
Plastic Mounting Clips 1 - Bottom; 1 - Top Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Heavy Steel - Powder Coat Finish	Black
Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant 5-year limited warranty Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Configuration	24in / 600mm Vertical Rackmount
Product Warranty 5-year limited warranty Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Plastic Mounting Clips	1 - Bottom; 1 - Top
Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Product Warranty	5-year limited warranty
Chassis Dimensions (LxWxD) 24.00in x 1.61in x 1.61in	Certification/Agency Approvals	RoHS Compliant
	Certification/Agency Approvals	UL & c-UL Listed 60950
Shipped Weight 5lbs (2.27kg)	Chassis Dimensions (LxWxD)	24.00in x 1.61in x 1.61in
	Shipped Weight	5lbs (2.27kg)