

## OVERVIEW

Basic surge protected rPDUs deliver reliable power to critical IT equipment within a rack or cabinet and comes equipped with built-in surge protection.

### Benefits

- Ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: 28153VH

**Model Number:** SPFN104-1025TL

**Category:** Basic

**Sub Category:** Surge

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Basic Surge, 20A, 120V, 1.9kW, Horizontal, (10) NEMA 5-20R, 10ft power cord with L5-20P, Black Powder Coat.

### Plug Form:



L5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 10)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|  |  |
|--|--|
| Quantity Of Inputs                     | 1  |
| Voltage                                | 100-120V   |
| Current                                | 20A  |
| VA per Input (Load Capacity)           | 1.9kW (120V)   |
| Frequency                              | 50/60Hz  |
| Over Current Protection                | 20A Thermal Breaker                                    |
| Switch                                 | No   |
| Indicators - LED(s)                    | 1 - Power ON Green LED                                 |
| Power Cable Wire Gauge                 | 12/3   |
| Power Cable Length                     | 10ft   |
| Plug Type                              | NEMA L5-20P Twistlock                                  |
| Receptacle/Socket Type #1              | NEMA 5-20R   |
| - Quantity on Face                     | 10   |
| - Quantity per Breaker                 | 10   |
| - Style                                | Duplex   |
| - Maximum Output per Receptacle/Socket | 20A  |
| - Voltage per Receptacle/Socket        | 120V   |
| Joule Rating                           | 720  |
| Maximum Clamping Voltage               | 340V   |
| Response Time                          | < 5 nanoseconds  |
| Technology Used                        | Super MOVs   |
| Surge Indicator Red LED                | Yes  |
| Continuous Operating Temperature Range | 10-45C / 50-113F                                       |
| Heavy Steel - Powder Coat Finish       | Black  |
| Configuration                          | 19in / 483mm Horizontal Rackmount                      |
| Adjustable Mount Brackets              | Yes  |
| Country of Origin                      | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty                       | 5-year limited warranty                                |
| Connected Equipment Warranty           | 5 years / \$5,000                                      |
| Certification/Agency Approvals         | RoHS Compliant   |
| Certification/Agency Approvals         | UL & c-UL Listed 60950                                 |
| Chassis Dimensions (HxWxD)             | 1.72in x 17in x 4.50in                                 |
| Shipped Weight                         | 7lbs (3.18kg)  |