

## OVERVIEW

Basic surge protected rPDUs deliver reliable power to critical IT equipment within a rack or cabinet and comes equipped with built-in surge protection.

### Benefits

- Ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



**Part #: 38045**

**Model Number:** SP124-1026

**Category:** Basic

**Sub Category:** Surge

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Surge, 20A, 120V, 1.9kW, Horizontal, (12) NEMA 5-20R, 10ft power cord with 5-20P, Black Powder Coat.

### Plug Form:



5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 12)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs

1

|   |  |
|---|--|
| <b>Voltage</b>                                | 100-120V   |
| <b>Current</b>                                | 20A  |
| <b>VA per Input (Load Capacity)</b>           | 1.9kW (120V)   |
| <b>Frequency</b>                              | 50/60Hz  |
| <b>Over Current Protection</b>                | 20A Thermal Breaker                                    |
| <b>Switch</b>                                 | Yes  |
| <b>Indicators - LED(s)</b>                    | 1 - Power ON Green LED                                 |
| <b>Power Cable Wire Gauge</b>                 | 12/3   |
| <b>Power Cable Length</b>                     | 10ft   |
| <b>Plug Type</b>                              | NEMA 5-20P   |
| <b>Receptacle/Socket Type #1</b>              | NEMA 5-20R   |
| <b>- Quantity on Face</b>                     | 2  |
| <b>- Quantity on Rear</b>                     | 10   |
| <b>- Quantity per Breaker</b>                 | 12   |
| <b>- Style</b>                                | Duplex   |
| <b>- Maximum Output per Receptacle/Socket</b> | 20A  |
| <b>- Voltage per Receptacle/Socket</b>        | 120V   |
| <b>Joule Rating</b>                           | 720  |
| <b>Maximum Clamping Voltage</b>               | 340V   |
| <b>Response Time</b>                          | < 5 nanoseconds  |
| <b>Technology Used</b>                        | Super MOVs   |
| <b>Surge Indicator Red LED</b>                | Yes  |
| <b>Continuous Operating Temperature Range</b> | 10-45C / 50-113F                                       |
| <b>Heavy Steel - Powder Coat Finish</b>       | Black  |
| <b>Configuration</b>                          | 19in / 483mm Horizontal Rackmount                      |
| <b>Flush Mount</b>                            | Yes  |
| <b>Country of Origin</b>                      | USA, TAA Compliant and Buy American Act COTS Compliant |
| <b>Product Warranty</b>                       | 5-year limited warranty                                |
| <b>Connected Equipment Warranty</b>           | 5 years / \$5,000                                      |
| <b>Certification/Agency Approvals</b>         | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>         | UL & c-UL Listed 60950                                 |
| <b>Chassis Dimensions (HxWxD)</b>             | 1.72in x 17in x 3.75in                                 |
| <b>Shipped Weight</b>                         | 7lbs (3.18kg)  |