

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: 38136

Model Number: VREBN200-103D20TL6

Category: Basic

Sub Category: Standard

Power Configuration: 30A, 208V, 4.9kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary:

rPDU, Basic Standard, 30A, 208V, 4.9kW, Vertical, (20) NEMA 6-20R, 10ft power cord with L6-30P, Black Powder Coat.

Plug Form:



L6-30P

Receptacle:



NEMA 6-20R
(Quantity: 20)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|------------------------------|--------------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 30A |
| VA per Input (Load Capacity) | 4.9kW (208V) |
| Frequency | 50/60Hz |

| | |
|--|--|
| Over Current Protection | (4) 15A Thermal Breakers |
| Switch | No |
| Power Cable Wire Gauge | 10/3 |
| Power Cable Length | 10ft |
| Plug Type | NEMA L6-30P Twistlock |
| Receptacle/Socket Type #1 | NEMA 6-20R |
| - Quantity on Face | 20 |
| - Quantity per Breaker Pair | 10 |
| - Style | Duplex |
| - Maximum Output per Receptacle/Socket | 15A |
| - Voltage per Receptacle/Socket | 208V |
| Continuous Operating Temperature Range | 10-45C / 50-113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 66in / 1683mm Vertical Rackmount |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | UL & c-UL Listed Accessory 1950 |
| Chassis Dimensions (LxWxD) | 66.25in x 1.85in x 1.61in |
| Shipped Weight | 15lbs (6.8kg) |