

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: 38156

**Model Number:** NSVC140-102S20TL

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 48in / 1207mm, Vertical

**Product Summary:** rPDU, Basic Standard, 20A, 120V, 1.9kW, Vertical, (14) NEMA 5-20R, 10ft power cord with L5-20P, Black Powder Coat.

### Plug Form:



L5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 14)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |              |
|------------------------------|--------------|
| Quantity Of Inputs           | 1            |
| Voltage                      | 100-120V     |
| Current                      | 20A          |
| VA per Input (Load Capacity) | 1.9kW (120V) |
| Frequency                    | 50/60Hz      |

|   |  |
|---|--|
| <b>Over Current Protection</b>                | 20A Thermal Breaker                                    |
| <b>Switch</b>                                 | Yes  |
| <b>Indicators - LED(s)</b>                    | 1 - Power ON Green LED                                 |
| <b>Power Cable Wire Gauge</b>                 | 12/3   |
| <b>Power Cable Length</b>                     | 10ft   |
| <b>Plug Type</b>                              | NEMA L5-20P Twistlock                                  |
| <b>Receptacle/Socket Type #1</b>              | NEMA 5-20R   |
| <b>- Quantity on Face</b>                     | 14   |
| <b>- Quantity per Breaker</b>                 | 14   |
| <b>- Style</b>                                | Individual - In-Line                                   |
| <b>- Maximum Output per Receptacle/Socket</b> | 20A  |
| <b>- Voltage per Receptacle/Socket</b>        | 120V   |
| <b>Center to Center Receptacle Spacing</b>    | 2.95   |
| <b>Continuous Operating Temperature Range</b> | 10-45C / 50-113F                                       |
| <b>Heavy Steel - Powder Coat Finish</b>       | Black  |
| <b>Configuration</b>                          | 48in / 1207mm Vertical Rackmount                       |
| <b>Plastic Mounting Clips</b>                 | 1 - Bottom; 1 - Top                                    |
| <b>Country of Origin</b>                      | USA, TAA Compliant and Buy American Act COTS Compliant |
| <b>Product Warranty</b>                       | 5-year limited warranty                                |
| <b>Certification/Agency Approvals</b>         | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>         | UL & c-UL Listed 60950                                 |
| <b>Chassis Dimensions (LxWxD)</b>             | 47.50in x 1.61in x 1.61in                              |
| <b>Shipped Weight</b>                         | 8lbs (3.63kg)  |