

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



**Part #: 38589**

**Model Number:** VHVLN102-102C13TL6

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 20A, 208V, 3.3kW

**Physical Configuration:** 17in / 432mm, Horizontal/Vertical

### Product Summary:

rPDU, Basic Standard, 20A, 208V, 3.3kW, Horizontal/Vertical, (10) IEC C13, 10ft power cord with L6-20P, Black Powder Coat.

### Plug Form:



L6-20P

### Receptacle:



IEC C13  
(Quantity: 10)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                    |          |
|--------------------|----------|
| Quantity Of Inputs | 1        |
| Voltage            | 200-240V |
| Current            | 20A      |

|  |  |
|--|--|
| VA per Input (Load Capacity)           | 3.3kW (208V)   |
| Frequency                              | 50/60Hz  |
| Over Current Protection                | None   |
| Switch                                 | No   |
| Power Cable Wire Gauge                 | 12/3   |
| Power Cable Length                     | 10ft   |
| Plug Type                              | NEMA L6-20P Twistlock                                  |
| Receptacle/Socket Type #1              | IEC C13  |
| - Quantity on Face                     | 10   |
| - Style                                | Banks of 5   |
| - Maximum Output per Receptacle/Socket | 15A per receptacle bank                                |
| - Voltage per Receptacle/Socket        | 208V   |
| Continuous Operating Temperature Range | 10-45C / 50-113F                                       |
| Heavy Steel - Powder Coat Finish       | Black  |
| Configuration                          | 17in / 432mm Vertical/Horizontal Rackmount             |
| 19in Panel Mount Brackets              | Yes  |
| SLB-4 Brackets                         | Yes  |
| Country of Origin                      | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty                       | 5-year limited warranty                                |
| Certification/Agency Approvals         | RoHS Compliant   |
| Certification/Agency Approvals         | UL & c-UL Listed 60950                                 |
| Chassis Dimensions (LxWxD)             | 17.00in x 1.72in x 1.61in                              |
| Shipped Weight                         | 6lbs (2.72kg)  |