

# **OVERVIEW**

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### **Benefits**

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard five-year limited warranty.



## Part #: 38642

Model Number: VHVLN082-102C13TL6

Category: Basic

Sub Category: Standard

Power Configuration: 20A, 208V, 3.3kW

Physical Configuration: 17in / 432mm, Horizontal/Vertical

**Product Summary:** rPDU, Basic Standard, 20A, 208V, 3.3kW, Horizontal/Vertical, (8) IEC C13, 10ft power

cord with L6-20P, Black Powder Coat.

#### **Plug Form:** Receptacle:





L6-20P



(Quantity: 8)

## **Chassis Color Options:**



To discuss color options, contact your local sales representative.

## **Product Specification and Options**

### **System Features**

Quantity Of Inputs	1
Voltage	200-240V
Current	20A
VA per Input (Load Capacity)	3.3kW (208V)

Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	12/3
Power Cable Length	10ft
Plug Type	NEMA L6-20P Twistlock
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	8
- Style	Banks of 4
- Maximum Output per Receptacle/Socket	15A per receptacle bank
- Voltage per Receptacle/Socket	208V
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	17in / 432mm Vertical/Horizontal Rackmount
19in Panel Mount Brackets	Yes
SLB-4 Brackets	Yes
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (LxWxD)	17.00in x 1.72in x 1.61in
Shipped Weight	6lbs (2.72kg)