

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



### Part #: EP0G01A1

**Model Number:** VCOAED0A09N0DXX

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 10A, 230V, 2.3kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU - Basic Standard, 10A, 230V, 2.3kW, 1U Horizontal, (9) Manual locking IEC C13, 3m power cord with C14, Black Powder Coat

### Plug Form:



C14

### Receptacle:



IEC C13  
(Quantity: 9)

### Product Specification and Options

#### System Features

Quantity Of Inputs	1
Voltage	230V
Current	10A
VA per Input (Load Capacity)	2.3kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.5mm <sup>2</sup> H05VVF
Power Cable Length	10ft / 3m

<b>Plug Type</b>	IEC60320 C14 (corded)
<b>Receptacle/Socket Type #1</b>	Manual Locking IEC C13
<b>- Quantity on Face</b>	9
<b>- Maximum Output per Receptacle/Socket</b>	10A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Maximum Operating Temperature</b>	45C / 113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	1U, Horizontal Rackmount
<b>Product Warranty</b>	Two-Year limited warranty
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Marked
<b>Chassis Dimensions (HxWxD)</b>	44.4mm x 435mm x 44mm
<b>Shipping Weight</b>	3.5 lbs (1.55 kg)