

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 2-year warranty.



Part #: EPOG80A0

Model Number: VC0AAE0A20B4DXX

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 1504mm, Vertical

Product Summary:

rPDU - Basic Standard, 16A, 230V, 3.6kW, 0U Vertical, (20) Manual locking IEC C13, (4) Manual locking IEC C19, 3m power cord 1P+N+E (IP44), Black Powder Coat

Plug Form:

1P+N+E (IP44)

Receptacle:IEC C13
(Quantity: 20)IEC C19
(Quantity: 4)**Product Specification and Options****System Features**

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm ² H07RN-F
Power Cable Length	10ft / 3m
Plug Type	IEC60309 1P + N + E, 16A, 250V, Splashproof IP44
Receptacle/Socket Type #1	Manual Locking IEC C13
- Quantity on Face	20
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Locking IEC C19
- Quantity on Face	4
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	1248 mm (vertical mounting bracket included)
Product Warranty	Two-Year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	1504 mm x 66 mm x 45 mm
Shipping Weight	6 kg