

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



## Part #: EP0G80A1

**Model Number:** VC0AFE0C14N0DXX

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 1204mm, Vertical

### Product Summary:

rPDU - Basic Standard, 16A, 230V, 3.6kW, 0U Vertical, (14) German Schuko, 3m power cord with German Schuko plug, Black Powder Coat

Plug Form:



Schuko

Receptacle:



German Schuko  
(Quantity: 14)

Product Specification and Options

System Features	
Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mmÂ² H05VVF
Power Cable Length	10ft / 3m
Plug Type	16A Schuko
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	14
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	936mm (vertical mounting bracket included)
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	1204mm x 66mm x 58mm
Shipping Weight	4 kg