

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G80A1

Model Number: VC0AFE0C14N0DXX

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 1204mm, Vertical

Product Summary:

rPDU - Basic Standard, 16A, 230V, 3.6kW, 0U Vertical, (14) German Schuko, 3m power cord with German Schuko plug, Black Powder Coat

Plug Form:



1P+N+E (IP44)

Receptacle:



German Schuko
(Quantity: 14)

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm ² H05VVF
Power Cable Length	10ft / 3m
Plug Type	16A Schuko
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	14
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	936mm (vertical mounting bracket included)
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	1204mm x 66mm x 58mm
Shipping Weight	4 kg