

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G80A2

Model Number: VC0ACE0A36B6DXX

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230/400V WYE, 11.0kW

Physical Configuration: 1954mm, Vertical

Product Summary:

rPDU - Basic Standard, 16A, 230/400V WYE, 11.0kW, 0U Vertical, (36) Manual locking IEC C13, (6) Manual locking IEC C19, 3m power cord 3P+N+E (IP44), Black Powder Coat

Plug Form:

3P+N+E (IP44)

Receptacle:IEC C13
(Quantity: 36)IEC C19
(Quantity: 6)**Product Specification and Options****System Features**

Quantity Of Inputs	1
Voltage	230/400V WYE
Current	16A x 3 Phase WYE
VA per Input (Load Capacity)	11.0kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	4mmÂ² H07RN-F
Power Cable Length	10ft / 3m
Plug Type	IEC60309 3P + N + E, 16A, 230/400V, Splashproof IP44
Receptacle/Socket Type #1	Manual Locking IEC C13
- Quantity on Face	36
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Locking IEC C19
- Quantity on Face	6
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	1872 mm (vertical mounting bracket included)
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	1954mm x 66 mm x 58 mm
Shipping Weight	8 kg