

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G81A1

Model Number: VC0AFD0C08N0DXX

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU - Basic Standard, 16A, 230V, 3.6kW, 1U Horizontal, (8) German Schuko, 3m power cord with German Schuko, Black Powder Coat

Plug Form:



Schuko

Receptacle:



German Schuko
(Quantity: 8)

Product Specification and Options

System Features

| | |
|------------------------------|----------------------------|
| Quantity Of Inputs | 1 |
| Voltage | 230V |
| Current | 16A |
| VA per Input (Load Capacity) | 3.6kW |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | No |
| Power Cable Wire Gauge | 2.5mm ² H07RN-F |
| Power Cable Length | 10ft / 3m |

| | |
|---|---|
| Plug Type | 16A Schuko |
| Receptacle/Socket Type #1 | German Schuko |
| - Quantity on Face | 8 |
| - Maximum Output per Receptacle/Socket | 16A |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 45C / 113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 1U, Horizontal Rackmount |
| Adjustable Mount Brackets | No |
| Product Warranty | Two-Year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | FCC Marked |
| Chassis Dimensions (HxWxD) | 44.4mm x 435mm x 44mm |
| Shipping Weight | 5.5lbs (2.5kg) |