

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G90A1

Model Number: VC0ABE2C18N0DXX

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 1504mm, Vertical

Product Summary:

rPDU - Basic Standard, 32A, 230V, 7.3kW, 0U Vertical, (18) German Schuko, 3m power cord with 1P+N+E (IP44), Black Powder Coat

Plug Form:

1P+N+E (IP44)

Receptacle:German Schuko
(Quantity: 18)**Product Specification and Options****System Features**

| | |
|---|--|
| Quantity Of Inputs | 1 |
| Voltage | 230V |
| Current | 32A |
| VA per Input (Load Capacity) | 7.3kW |
| Frequency | 50/60Hz |
| Over Current Protection | (2) 16A Single Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 4mmÂ² H07RN-F |
| Power Cable Length | 10ft / 3m |
| Plug Type | IEC60309 1P + N + E, 32A, 250V, Splashproof IP44 |
| Receptacle/Socket Type #1 | German Schuko |
| - Quantity on Face | 18 |
| - Maximum Output per Receptacle/Socket | 16A |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 45C / 113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | Zero U |
| Toolless Mounting Hardware - Center to Center Spacing | 1248 mm (vertical mounting bracket included) |
| Product Warranty | One Year |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | FCC Marked |
| Chassis Dimensions (LxWxD) | 1504 mm x 66mm x 58mm |
| Shipping Weight | 6.3 kg |