

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



Part #: EP0G90A2

Model Number: VC0ADE6A30BCDXX

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230/400V WYE, 22.0kW

Physical Configuration: 2150mm, Vertical

Product Summary:

rPDU - Basic Standard, 32A, 230/400V WYE, 22.0kW, 0U Vertical, (30) Manual locking IEC C13, (12) Manual locking IEC C19, 3m power cord 3P+N+E (IP44), Black Powder Coat

Plug Form:

3P+N+E (IP44)

Receptacle:IEC C13
(Quantity: 30)IEC C19
(Quantity: 12)**Product Specification and Options****System Features**

Quantity Of Inputs	1
Voltage	230/400V WYE
Current	32A
VA per Input (Load Capacity)	22.0kW
Frequency	50/60Hz
Over Current Protection	(6) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	6mm ² H07RN-F
Power Cable Length	10ft / 3m
Plug Type	IEC60309 3P + N + E, 32A, 230/400V, Splashproof IP44
Receptacle/Socket Type #1	Manual Locking IEC C13
- Quantity on Face	30
- Quantity per Breaker	5
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Locking IEC C19
- Quantity on Face	12
- Quantity per Breaker	2
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	2028mm (vertical mounting bracket included)
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	2154mm x 66mm x 58mm
Shipping Weight	11.7 kg

