

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Every unit is 100% tested for reliability and functionality
- Simple and convenient configuration
- Standard 1 year warranty.



## Part #: EP0G90A2

**Model Number:** VCOADE6A30BCDXX

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230/400V WYE, 22.0kW

**Physical Configuration:** 2150mm, Vertical

### Product Summary:

rPDU - Basic Standard, 32A, 230/400V WYE, 22.0kW, 0U Vertical, (30) Manual locking IEC C13, (12) Manual locking IEC C19, 3m power cord 3P+N+E (IP44), Black Powder Coat

**Plug Form:**

3P+N+E (IP44)

**Receptacle:**IEC C13  
(Quantity: 30)IEC C19  
(Quantity: 12)**Product Specification and Options****System Features**

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	230/400V WYE
<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	22.0kW
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(6) 16A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	6mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	10ft / 3m
<b>Plug Type</b>	IEC60309 3P + N + E, 32A, 230/400V, Splashproof IP44
<b>Receptacle/Socket Type #1</b>	Manual Locking IEC C13
<b>- Quantity on Face</b>	30
<b>- Quantity per Breaker</b>	5
<b>- Maximum Output per Receptacle/Socket</b>	10A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Receptacle/Socket Type #2</b>	Manual Locking IEC C19
<b>- Quantity on Face</b>	12
<b>- Quantity per Breaker</b>	2
<b>- Maximum Output per Receptacle/Socket</b>	16A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Maximum Operating Temperature</b>	45C / 113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	Zero U
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	2028mm (vertical mounting bracket included)
<b>Product Warranty</b>	Two-Year limited warranty
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Marked
<b>Chassis Dimensions (LxWxD)</b>	2154mm x 66mm x 58mm
<b>Shipping Weight</b>	11.7 kg

