# Vertiv<sup>™</sup> PowerGo rPDU



## **OVERVIEW**

Unit Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering a comprehensive view of input level power usage via remote network access.

#### **Benefits**

- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs.
- Standard 1 year warranty.

AND AND THE PARTICULAR STANDARD STANDAR

# Part #: EP4G80A2

Model Number: VC1HCC0A30B6DXX

Category: Monitored
Sub Category: Unit Level

Power Configuration: 16A, 230/400V WYE, 11.0kW Physical Configuration: 75in / 1905mm, Vertical

Product Summary: rPDU - Monitored Unit Level, 16A, 230/400V, 11kW, 0U Vertical, (30) Manual locking

IEC C13, (6) Manual locking IEC C19, 3m power cord with 3P + N + E, Black Powder

Coat

#### **Monitoring:**

Input power monitoring. Daisy chain Ethernet connectivity. Local high visibility display.

### Receptacle:





(Quantity: 30)

(Quantity: 6)

### **Product Specification and Options**

#### **System Features**

Monitoring	Input power monitoring. Daisy chain Ethernet connectivity. Loca high visibility display.
Monitoring Level 1	Aggregate - Total Unit Monitoring (kWh, W, VA, PF)
Monitoring Level 2	Phase (A, B, C) Monitoring (kWh, W, VA, PF, V, A)
Quantity Of Inputs	1
Voltage	230/400V WYE
Current	16A x 3 Phase WYE
VA per Input (Load Capacity)	11.0kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Scrolling / Rotatable Digital Display	Yes
Power Cable Wire Gauge	4mm² H07RN-F
Power Cable Length	10ft / 3m
Plug Type	IEC60309 3P + N + E, 16A, 230/400V, Splashproof IP44
Receptacle/Socket Type #1	Manual Locking IEC C13
- Quantity on Face	30
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Locking IEC C19
- Quantity on Face	6
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Network Connection	Dual 10/100Mbps Ethernet
Protocols Supported	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP
Data Access Formats	CSV datalog, JSON API, JSON datalog
IP Reset Button	Yes
Hard Reboot Button	Yes
Maximum Operating Temperature	45C / 113F
Heavy Steel - Powder Coat Finish	Black

Configuration	Zero U
Toolless Mounting Hardware - Center to Center Spacing	1560mm and 1645mm (vertical mounting bracket included)
Product Warranty	One Year
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	FCC Marked
Chassis Dimensions (LxWxD)	1905mm x 51mm x 51mm
Shipping Weight	9.25 kg