

## OVERVIEW

Unit Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering a comprehensive view of input level power usage via remote network access.

### Benefits

- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs.
- Standard 1 year warranty.



## Part #: EP4G81A0

**Model Number:** VC1HFA0C06N0DXX

**Category:** Monitored

**Sub Category:** Unit Level

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 19in / 483mm, Horizontal


### Product Summary:

rPDU - Monitored Unit Level, 16A, 230V, 3.6kW, 1U Horizontal, (6) German Schuko, 3m power cord with German Schuko, Black Powder Coat

### Monitoring:

Input power monitoring. Daisy chain Ethernet connectivity. Local high visibility display.

### Receptacle:



German Schuko  
(Quantity: 6)

## Product Specification and Options

### System Features

#### Monitoring

Input power monitoring. Daisy chain Ethernet connectivity. Local high visibility display.

#### Monitoring Level 1

Phase (A) Monitoring (kWh, W, VA, PF, V, A)

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	230V
<b>Current</b>	16A
<b>VA per Input (Load Capacity)</b>	3.6kW
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	None
<b>Switch</b>	No
<b>Scrolling / Rotatable Digital Display</b>	Yes
<b>Power Cable Wire Gauge</b>	2.5mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	10ft / 3m
<b>Plug Type</b>	16A Schuko
<b>Receptacle/Socket Type #1</b>	German Schuko
<b>- Quantity on Face</b>	6
<b>- Maximum Output per Receptacle/Socket</b>	16A
<b>- Voltage per Receptacle/Socket</b>	230V
<b>Network Connection</b>	Dual 10/100Mbps Ethernet
<b>Protocols Supported</b>	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP
<b>Data Access Formats</b>	CSV datalog, JSON API, JSON datalog
<b>IP Reset Button</b>	Yes
<b>Hard Reboot Button</b>	Yes
<b>Maximum Operating Temperature</b>	45C / 113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	1U, Horizontal Rackmount
<b>Adjustable Mount Brackets</b>	No
<b>Product Warranty</b>	Two-Year limited warranty
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	FCC Marked
<b>Chassis Dimensions (HxDxW)</b>	44mm x 435mm x 165mm
<b>Shipping Weight</b>	9.5 lbs (4.3 kg)