

OVERVIEW

The Vertiv Geist FSC, Facility Side Cable, features a universal connector designed to mate with the Universal Input on the Vertiv Geist UPDU, Universal Power Distribution Unit. The FSC is available in common worldwide AC power specs ranging from 16A to 60A, 120V to 415V with single and three phase power configurations. Select the detachable Vertiv Geist FSC specific to the local power configuration to power the UPDU. (UPDU sold separately)

Benefits

- The flexibility offered by the UPDU and FSC enable any rack architecture to be installed in any data center around the world, regardless of the power infrastructure already in place.
- The FSC enables users to utilize a single UPDU model with various input power configurations to simplify global IT infrastructure deployments, inventory management and enable rapid deployments worldwide.
- Increase or decrease UPDU power capacity by changing the FSC to adapt to fluctuating equipment power needs.
- Every unit is 100% tested for reliability and functionality to ensure units function as designed.



Part #: FSC1U001

Model Number: CSU-S02A7-43000-3PS6B-S

Category: Facility Side Cable Sub Category: Standard

Power Configuration: 30/32A, 200-240V, 7.3kW

Product Summary: rPDU, Facility Side Cable Standard, 5.7 to 7.3kW, Variable Power Configuration, 10ft /

3m power cord with 2P+E (IP44)

Plug Form:



2P+E (IP44)

Product Specification and Options

System Features

Compatibility

For use with Vertiv Geist Universal Rack PDU (UPDU)

| Voltage | 200-240V |
|------------------------------------|--|
| Current | 30/32A |
| Frequency | 50/60Hz |
| Power Cable Wire Gauge | 9/3 (6mm² H07RN-F) |
| Power Cable Length | 10ft / 3m |
| Plug Type | IEC60309 2P + E, 30/32A, 250V, Splashproof IP44 |
| Max Plug kW | 5.7kW (240V@24A Derated UL) or 7.3kW (230V@32A CE) |
| Output Connector | Universal Connector |
| UPDU Voltage per Receptacle/Socket | 208-240V |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Shipped Weight | 6lbs (2.72kg) |
| | |