

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: G1032

**Model Number:** MG00X4B0-30IN63-2PS6B2A10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 16A, 230V, 3.6kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Basic Standard, 16A, 230V, 3.6kW, Vertical, (24) IEC C13, (6) IEC C19, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 24)



IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	16A
VA per Input (Load Capacity)	3.6kW (230V)
Frequency	50/60Hz

Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mmÂ² H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 16A, 250V, Splashproof IP44
Combined Total Receptacle/Socket Quantity	30
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	24
- Style	Banks of 4
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC C19
- Quantity on Face	6
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	66in / 1683mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes
Toolless Mounting Hardware - Center to Center Spacing	1556mm and 1645mm
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	RCM Mark (EMC Only)
Certification/Agency Approvals	C <sub>p</sub> Mark
Chassis Dimensions (LxWxD)	1683mm x 51mm x 51mm
Shipped Weight	15lbs (6.8kg)