

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard five-year limited warranty.



Part #: G2102

Model Number: MG00XER0-06UKL3-7UKA6H10-S

Category: Basic

Sub Category: Standard

Power Configuration: 13A, 230V, 2.9kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Basic Standard, 13A, 230V, 2.9kW, Horizontal, (6) BS1363, 3m power cord with

BS1363, Black Powder Coat.

Plug Form: Receptacle:





BS1363

BS1363 (Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

1 **Quantity Of Inputs** Voltage 200-240V

| Current | 13A |
|--|---|
| VA per Input (Load Capacity) | 2.9kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | Green neon with protective cover |
| Power Cable Wire Gauge | 1.5mm² PVC |
| Power Cable Length | 3m |
| Plug Type | BS 1363P |
| Receptacle/Socket Type #1 | BS1363 |
| - Quantity on Face | 6 |
| - Style | Individual |
| - Maximum Output per Receptacle/Socket | 13A |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 19in / 483mm Horizontal Rackmount |
| Flush Mount | Yes |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | C _o Mark |
| Chassis Dimensions (HxWxD) | 44mm x 435mm x 75mm |
| Shipped Weight | 4lbs (1.81kg) |
| | |