

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2104

Model Number: MG00XMR0-08UKL3-7UKA6H10-S

Category: Basic

Sub Category: Standard

Power Configuration: 13A, 230V, 2.9kW

Physical Configuration: 19in / 483mm, Horizontal


Product Summary: rPDU, Basic Standard, 13A, 230V, 2.9kW, Horizontal, (8) BS1363, 3m power cord with BS1363, Black Powder Coat.

Plug Form:



BS1363

Receptacle:



BS1363
(Quantity: 8)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	13A
VA per Input (Load Capacity)	2.9kW (230V)

Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.5mm ² PVC
Power Cable Length	3m
Plug Type	BS 1363P
Receptacle/Socket Type #1	BS1363
- Quantity on Face	8
- Style	Individual
- Maximum Output per Receptacle/Socket	13A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Flush Mount	Yes
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C _ϕ Mark
Chassis Dimensions (HxWxD)	44mm x 435mm x 75mm
Shipped Weight	4lbs (1.81kg)