

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: G2118

Model Number: MG00XEBO-15UKR3-3PS6B2A10-S

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 66in / 1683mm, Vertical


Product Summary: rPDU, Basic Standard, 32A, 230V, 7.3kW, Vertical, (15) BS1363, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Plug Form:



1P+N+E (IP44)

Receptacle:



BS1363
(Quantity: 15)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz

Over Current Protection	None
Switch	No
Power Cable Wire Gauge	4mm ² H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
Receptacle/Socket Type #1	BS1363
- Quantity on Face	15
- Style	Individual - Right Hand Angled
- Maximum Output per Receptacle/Socket	13A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	66in / 1683mm Vertical Rackmount
GE Vertical Mounting Bracket	Yes
Toolless Mounting Hardware - Center to Center Spacing	1556mm and 1645mm
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C _p Mark
Chassis Dimensions (LxWxD)	1683mm x 54mm x 50mm
Shipped Weight	14lbs (6.35kg)