

# **OVERVIEW**

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### **Benefits**

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard five-year limited warranty.



## Part #: G2160

Model Number: MG00XER0-08UKL3-2PS6B2H10-S

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Standard, 16A, 230V, 3.6kW, Horizontal, (8) BS1363, 3m power cord with

1P+N+E (IP44), Black Powder Coat.

#### **Plug Form:** Receptacle:





1P+N+E (IP44)

BS1363 (Quantity: 8)

## **Chassis Color Options:**



To discuss color options, contact your local sales representative.

## **Product Specification and Options**

### **System Features**

Quantity Of Inputs	1
Voltage	200-240V
Current	16A
VA per Input (Load Capacity)	3.6kW (230V)

Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm² H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 16A, 250V, Splashproof IP44
Receptacle/Socket Type #1	BS1363
- Quantity on Face	8
- Style	Individual
- Maximum Output per Receptacle/Socket	13A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Flush Mount	Yes
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C <sub>P</sub> Mark
Chassis Dimensions (HxWxD)	44mm x 435mm x 50mm
Shipped Weight	4lbs (1.81kg)