

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2175

Model Number: MG00XER0-12C133-7UKA6H10-S

Category: Basic

Sub Category: Standard

Power Configuration: 13A, 230V, 2.9kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Basic Standard, 13A, 230V, 2.9kW, Horizontal, (12) IEC C13, 3m power cord with BS1363, Black Powder Coat.

Plug Form:



BS1363

Receptacle:



IEC C13
(Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--------------------|----------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 13A |

| | |
|--|---|
| VA per Input (Load Capacity) | 2.9kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | None |
| Switch | Green neon with protective cover |
| Power Cable Wire Gauge | 1.5mm ² PVC |
| Power Cable Length | 3m |
| Plug Type | BS 1363P |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 12 |
| - Style | Banks of 6 |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 19in / 483mm Horizontal Rackmount |
| Flush Mount | Yes |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | C _P Mark |
| Chassis Dimensions (HxWxD) | 44mm x 435mm x 100mm |
| Shipped Weight | 4lbs (1.81kg) |