

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: G2195

Model Number: MG00XEB1-30C133-3PS6B2A10-S

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary:

rPDU, Basic Standard, 32A, 230V, 7.3kW, Vertical, (30) IEC C13, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Plug Form:



1P+N+E (IP44)

Receptacle:



IEC C13
(Quantity: 30)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|------------------------------|--------------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 32A |
| VA per Input (Load Capacity) | 7.3kW (230V) |
| Frequency | 50/60Hz |

| | |
|--|--|
| Over Current Protection | None |
| Over Current Protection | (2) 16A Single Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 4mm ² H07RN-F |
| Power Cable Length | 3m |
| Plug Type | IEC60309 1P + N + E, 32A, 250V, Splashproof IP44 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 30 |
| - Quantity per Breaker | 15 |
| - Style | 2 Individual, 14 Banks of 2 |
| - Maximum Output per Receptacle/Socket | 10A per receptacle bank |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 66in / 1683mm Vertical Rackmount |
| GE Vertical Mounting Bracket | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 1556mm and 1645mm |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | Complies with IEC 62368-1 (DOC Available) |
| Certification/Agency Approvals | Complies with EN 55032 and EN 55035 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | RCM Mark (EMC Only) |
| Certification/Agency Approvals | C ₁ Mark |
| Chassis Dimensions (LxWxD) | 1683mm x 50mm x 50mm |
| Doghouse (D) | 37mm |
| Shipped Weight | 13lbs (5.9kg) |