

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: I10401

**Model Number:** MN01X4W1-36MR99-3TL14A0A10-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 120/208V, 5.7kW

**Physical Configuration:** 70in / 1778mm, Vertical

### Product Summary:

rPDU, Basic Upgradeable, 30A, 120/208V, 5.7kW, Vertical, (20) IEC C13, (4) IEC C19, (12) NEMA 5-20R, 10ft power cord with L14-30P, Black Powder Coat.

### Monitoring:

No Monitoring (Upgradeable with IMD module)

Plug Form:



L14-30P

Receptacle:



IEC C13  
(Quantity: 20)



IEC C19  
(Quantity: 4)



NEMA 5-20R  
(Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

|   |   |
|---|---|
| Monitoring                                | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs                        | 1   |
| Voltage                                   | 100-120/200-240V                            |
| Current                                   | 30A   |
| VA per Input (Load Capacity)              | 5.7kW (208V)                                |
| Frequency                                 | 50/60Hz                                     |
| Over Current Protection                   | (2) 20A Double Pole Magnetic Breakers       |
| Switch                                    | Breaker/Switch Combination                  |
| Power Cable Wire Gauge                    | 10/4  |
| Power Cable Length                        | 10ft / 3m                                   |
| Power Entry Location                      | Bottom Front                                |
| Plug Type                                 | NEMA L14-30P Twistlock                      |
| Combined Total Receptacle/Socket Quantity | 36  |
| Receptacle/Socket Type #1                 | IEC C13                                     |
| - Quantity on Face                        | 20  |
| - Quantity per Breaker                    | 10  |
| - Style                                   | Banks of 5                                  |
| - Voltage per Receptacle/Socket           | 208V  |
| Receptacle/Socket Type #2                 | IEC C19                                     |
| - Quantity on Face                        | 4   |
| - Quantity per Breaker                    | 2   |
| - Style                                   | Individual                                  |
| - Voltage per Receptacle/Socket           | 208V  |
| Receptacle/Socket Type #3                 | NEMA 5-20R                                  |
| - Quantity on Face                        | 12  |
| - Quantity per Breaker                    | 6   |
| - Style                                   | Duplex                                      |
| - Voltage per Receptacle/Socket           | 120V  |

|   |  |
|---|--|
| Maximum Operating Temperature                         | 60C / 140F   |
| Heavy Steel - Powder Coat Finish                      | Black  |
| Configuration   | 70in / 1778mm Vertical Rackmount                       |
| 7938 Vertical Mounting Bracket Kit                    | Yes  |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in                                    |
| Country of Origin                                     | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty                                      | 5-year limited warranty                                |
| Certification/Agency Approvals                        | UL & c-UL Listed 62368-1                               |
| Certification/Agency Approvals                        | RoHS Compliant   |
| Certification/Agency Approvals                        | FCC Part 15 Class A Conformance                        |
| Chassis Dimensions (LxWxD)                            | 70in x 2in x 2in                                       |
| Shipped Weight  | 17lbs (7.71kg)   |