

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: I10488

**Model Number:** MN01X4W1-36CF18-3TL15A0A10-S-A

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 30A, 208V DELTA, 8.6kW

**Physical Configuration:** 70in / 1778mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 30A, 208V DELTA, 8.6kW, Vertical, (36) Combination C13/C19, 10ft power cord with L15-30P, Black Powder Coat.


**Monitoring:** No Monitoring (Upgradeable with IMD module)

### Plug Form:



L15-30P

### Receptacle:



Combination C13/C19  
(Quantity: 36)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                    |   |
|--------------------|---|
| Monitoring         | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs | 1   |
| Voltage            | 200-240V Delta                              |

|  |  |
|--|--|
| <b>Current</b>   | 30A x 3 Phase DELTA                                    |
| <b>VA per Input (Load Capacity)</b>                          | 8.6kW (208V)   |
| <b>Frequency</b>   | 50/60Hz  |
| <b>Over Current Protection</b>                               | (3) 20A Double Pole Magnetic Breakers (22kAIC Rated)   |
| <b>Switch</b>  | Breaker/Switch Combination                             |
| <b>Power Cable Wire Gauge</b>                                | 10/4   |
| <b>Power Cable Length</b>                                    | 10ft / 3m  |
| <b>Power Entry Location</b>                                  | Bottom Front   |
| <b>Plug Type</b>   | NEMA L15-30P Twistlock                                 |
| <b>Alternating Phase/Circuits</b>                            | Yes  |
| <b>Receptacle/Socket Type #1</b>                             | Combination C13/C19                                    |
| <b>- Quantity on Face</b>                                    | 36   |
| <b>- Quantity per Breaker and Phase Combination</b>          | 12   |
| <b>- Circuit Color ID</b>                                    | 3 Circuit = Orange, Green, Blue                        |
| <b>- Style</b>   | Banks of 6   |
| <b>- Voltage per Receptacle/Socket</b>                       | 208V   |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F   |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black  |
| <b>Configuration</b>   | Zero U   |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes  |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm                |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant |
| <b>Product Warranty</b>                                      | 5-year limited warranty                                |
| <b>Certification/Agency Approvals</b>                        | UL & c-UL Listed 62368-1                               |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>                        | FCC Part 15 Class A Conformance                        |
| <b>Chassis Dimensions (LxWxD)</b>                            | 70in x 2in x 2in / 1778mm x 51mm x 51mm                |
| <b>Shipped Weight</b>  | 17lbs (7.71kg)   |