

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: PI10001

Model Number: MP01X4W1-42IZ68-3JL6A5A10-S

Category: Basic

Sub Category: Upgradeable

Power Configuration: 30A, 200V, 6.0kW

Physical Configuration: 70in / 1778mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 30A, 200V, 6.0kW, Vertical, (36) IEC C13, (6) IEC C19, 3m power cord with L6-30P, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



L6-30P

Receptacle:



IEC C13
(Quantity: 36)



IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring

No Monitoring (Upgradeable with IMD module)

Quantity Of Inputs	1
Voltage	200-240V
Current	30A
VA per Input (Load Capacity)	6.0kW (200V)
Frequency	50/60Hz
Over Current Protection	(2) 20A Double Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	5.5mmÂ²
Power Cable Length	10ft / 3m
Power Entry Location	Bottom Front
Plug Type	JIS C8303, 2P/3W, 30A, 250V Locking, NEMA L6-30P
Combined Total Receptacle/Socket Quantity	42
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	36
- Quantity per Breaker	18
- Style	Banks of 6
- Voltage per Receptacle/Socket	200V
Receptacle/Socket Type #2	IEC C19
- Quantity on Face	6
- Quantity per Breaker	3
- Style	Individual
- Voltage per Receptacle/Socket	200V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	70in / 1778mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes
Toolless Mounting Hardware - Center to Center Spacing	1556mm and 1645mm
Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	METI DENAN
Chassis Dimensions (LxWxD)	1778mm x 51mm x 51mm
Shipped Weight	16lbs (7.26kg)