

OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: PI10025L

Model Number: MP01X4W1-30PN68-3JL15A5A10-S-A

Category: Basic

Sub Category: Upgradeable

Power Configuration: 30A, 200V DELTA, 10.3kW

Physical Configuration: 72in / 1829mm, Vertical

Product Summary: rPDU, Basic Upgradeable, 30A, 200V DELTA, 10.3kW, Vertical, (24) Locking IEC C13, (6) Locking IEC C19, 3m power cord with L15-30P, Black Powder Coat.

Monitoring: No Monitoring (Upgradeable with IMD module)

Plug Form:



L15-30P

Receptacle:



Locking IEC C13
(Quantity: 24)



Locking IEC C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring

No Monitoring (Upgradeable with IMD module)

| | |
|---|---|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V Delta |
| Current | 30A x 3 Phase DELTA |
| VA per Input (Load Capacity) | 10.3kW (200V) |
| Frequency | 50/60Hz |
| Over Current Protection | (3) 20A Double Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 5.5mmÂ² |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Bottom Front |
| Plug Type | JIS C8303, 3P/4W, 30A, 250V 3~ Locking, NEMA L15-30P |
| Combined Total Receptacle/Socket Quantity | 30 |
| Alternating Phase/Circuits | Yes |
| Receptacle/Socket Type #1 | U-Lock IEC C13 |
| - Quantity on Face | 24 |
| - Quantity per Breaker and Phase Combination | 8 |
| - U-Lock Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 200V |
| Receptacle/Socket Type #2 | U-Lock IEC C19 |
| - Quantity on Face | 6 |
| - Quantity per Breaker and Phase Combination | 2 |
| - U-Lock Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Individual |
| - Voltage per Receptacle/Socket | 200V |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 72in / 1829mm Vertical Rackmount |
| 7938 Vertical Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 1556mm and 1645mm |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | METI DENAN |
| Chassis Dimensions (LxWxD) | 1829mm x 51mm x 51mm |
| Shipped Weight | 17lbs (7.71kg) |