

## OVERVIEW

Upgradeable Metered rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet while delivering a view of real-time view of power usage from a local LED display.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform metered rPDUs to monitored rPDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



## Part #: PI10030L

**Model Number:** MP01D4B0-26PJ68-2JL6A5A10-S

**Category:** Metered

**Sub Category:** Upgradeable

**Power Configuration:** 20A, 200V, 4.0kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Metered Upgradeable, 20A, 200V, 4.0kW, Vertical, (20) Locking IEC C13, (6) Locking IEC C19, 3m power cord with L6-20P, Black Powder Coat.

### Monitoring:

Input current monitoring. Local high visibility LED display.

### Plug Form:



L6-20P

### Receptacle:



Locking IEC C13  
(Quantity: 20)



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

#### Monitoring

Input current monitoring. Local high visibility LED display.

|  |   |
|--|---|
| <b>Monitoring Level 1</b>                                    | Phase (A) Monitoring (kWh, W, VA, PF, V, A)   |
|  | Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements           |
| <b>Quantity Of Inputs</b>                                    | 1   |
| <b>Voltage</b>   | 200-240V  |
| <b>Current</b>   | 20A   |
| <b>VA per Input (Load Capacity)</b>                          | 4.0kW (200V)  |
| <b>Frequency</b>   | 50/60Hz   |
| <b>Over Current Protection</b>                               | None  |
| <b>Switch</b>  | No  |
| <b>Scrolling / Rotatable Digital Display</b>                 | Yes   |
| <b>Power Cable Wire Gauge</b>                                | 3.5mmÂ²   |
| <b>Power Cable Length</b>                                    | 10ft / 3m   |
| <b>Power Entry Location</b>                                  | Bottom Front  |
| <b>Plug Type</b>   | JIS C8303, 2P/3W, 20A, 250V Locking, NEMA L6-20P  |
| <b>Combined Total Receptacle/Socket Quantity</b>             | 26  |
| <b>Receptacle/Socket Type #1</b>                             | U-Lock IEC C13  |
| - Quantity on Face   | 20  |
| - U-Lock Color ID  | 1 Circuit = Orange  |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                              | 200V  |
| <b>Receptacle/Socket Type #2</b>                             | U-Lock IEC C19  |
| - Quantity on Face   | 6   |
| - U-Lock Color ID  | 1 Circuit = Orange  |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                              | 200V  |
| <b>Internal RMS Voltage Sensor</b>                           | Yes   |
| <b>Internal RMS Current Sensor</b>                           | Yes   |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black   |
| <b>Configuration</b>   | 66in / 1683mm Vertical Rackmount  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 1556mm and 1645mm   |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant  |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | METI DENAN  |
| <b>Chassis Dimensions (LxWxD)</b>                            | 1683mm x 51mm x 51mm  |
| <b>Shipped Weight</b>  | 15lbs (6.8kg)   |