

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: U1075

Model Number: DU00X4W1-42CF17-1S02A9K00-S-A

Category: Basic

Sub Category: Standard

Power Configuration: Variable, Variable, 11.0kW

Physical Configuration: 72in / 1829mm, Vertical

Product Summary:

rPDU, Basic Standard, 11.0kW, Variable Power Configuration, Vertical, (42) Combination C13/C19, Universal Inlet, Black Powder Coat.

Plug Form:



Universal Inlet

Receptacle:



Combination C13/C19
(Quantity: 42)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--|---|
| Quantity Of Inputs | 1 |
| Maximum Input Power (Defined by Facility Side Cable) | 48A Single Phase, 240V Max, 11.0kW 24A 3 Phase DELTA, 240V Max, 8.6kW 16A Three Phase WYE, 240/415V Max, 11.0kW |
| Frequency | 50/60Hz |
| Over Current Protection | (3) 16A Double Pole Magnetic Breakers (10kAIC Rated) |

| | |
|--|---|
| Switch | Breaker/Switch Combination |
| Power Entry Location | Pivoting Connector |
| Plug Type | Universal Inlet |
| Alternating Phase/Circuits | Yes |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Face | 42 |
| - Quantity per Breaker | 14 |
| - Circuit Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | Defined by Facility Side Cable |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | Zero U |
| 4689 UPDU Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in / 1556mm and 1645mm |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | RoHS Compliant |
| Chassis Dimensions (LxWxD) | 70.0in x 2.0in x 2.25in |
| Doghouse (D) | 1.4in / 36mm |
| Shipped Weight | 19lbs (8.62kg) |