

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis
- Standard five-year limited warranty.



Part #: U1076

Model Number: DU00X1R1-12CF17-1S02A9H00-S

Category: Basic

Sub Category: Standard

Power Configuration: Variable, Max 11.0kW Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU, Basic Standard, Max 11.0kW, Variable Power Configuration, Horizontal, (12)

Combination C13/C19, Universal Inlet, Black Powder Coat.

Plug Form: Receptacle:







Combination C13/C19 (Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| Quantity Of Inputs | 1 |
|--|---|
| Maximum Input Power (Defined by Facility Side Cable) | 48A Single Phase, 240V Max, 11.0kW 24A 3 Phase DELTA, 240V Max, 8.6kW 16A Three Phase WYE, 240/415V Max, 11.0kW |
| Frequency | 50/60Hz |
| Over Current Protection | (3) 16A Double Pole Magnetic Breakers (10kAIC Rated) |
| Switch | Breaker/Switch Combination |

| Power Entry Location | Rear |
|----------------------------------|--|
| Plug Type | Universal Inlet |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Face | 12 |
| - Quantity per Breaker | 4 |
| - Circuit Color ID | 3 Circuit = Orange, Green, Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | Defined by Facility Side Cable |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 1U |
| Adjustable Mount Brackets | Yes |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | RoHS Compliant |
| Chassis Dimensions (HxWxD) | 1.72in x 17in x 9in / 44mm x 432mm x 229mm |
| Shipped Weight | 16lbs (7.26kg) |