

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: U1077

Model Number: DU00X2R1-24CF17-2S02A9H00-S

Category: Basic

Sub Category: Standard

Power Configuration: Variable, Variable, 22.0kW

Physical Configuration: 19in / 483mm, Horizontal


Product Summary: rPDU, Basic Standard, 22.0kW, Variable Power Configuration, Horizontal, (24) Combination C13/C19, Universal Inlet, Black Powder Coat.

Plug Form:



Universal Inlet

Receptacle:



Combination C13/C19
(Quantity: 24)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|--|--|
| Quantity Of Inputs | 1 |
| Maximum Input Power (Defined by Facility Side Cable) | 63A Single Phase, 240V Max, 14.4kW 48A 3 Phase DELTA, 240V Max, 19.9kW 32A Three Phase WYE, 240/415V Max, 22.0kW |
| Frequency | 50/60Hz |
| Over Current Protection | (6) 16A Double Pole Magnetic Breakers (10kAIC Rated) |

| | |
|----------------------------------|--|
| Switch | Breaker/Switch Combination |
| Power Entry Location | Left Rear |
| Plug Type | Universal Inlet |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Rear | 24 |
| - Quantity per Breaker | 4 |
| - Circuit Color ID | 6 Circuit = Orange, Light Orange, Green, Light Green, Blue, Light Blue |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | Defined by Facility Side Cable |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 2U |
| 19in Recess Mount | Yes |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | CE Marked |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Certification/Agency Approvals | UKCA Marked |
| Certification/Agency Approvals | RoHS Compliant |
| Chassis Dimensions (HxWxD) | 3.39in x 17in x 9in / 87mm x 432mm x 229mm |
| Shipped Weight | 16lbs (7.26kg) |