

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: UI10001L

**Model Number:** MU01X4W0-42PZ67-2C20A9A00-S

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 16A OR 20A, 120V OR 208V OR 230V, 1.9kW or 3.3kW or 3.6kW

**Physical Configuration:** 72in / 1829mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 16A OR 20A, 120V OR 208V OR 230V, 1.9kW or 3.3kW or 3.6kW, Vertical, (36) Locking IEC C13, (6) Locking IEC C19, C20, Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

### Plug Form:



C20

### Receptacle:



Locking IEC C13  
(Quantity: 36)



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

**Monitoring** No Monitoring (Upgradeable with IMD module)

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	100-240V
<b>Current</b>	16A or 20A
<b>VA per Input (Load Capacity)</b>	1.9kW (120V), 3.3kW (208V), 3.6kW (230V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	None
<b>Switch</b>	No
<b>Power Entry Location</b>	Bottom Front
<b>Plug Type</b>	IEC60320 C20 Power Inlet (cord sold separately)
<b>Combined Total Receptacle/Socket Quantity</b>	42
<b>Receptacle/Socket Type #1</b>	U-Lock IEC C13
- Quantity on Face	36
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100-120V or 208-240V
<b>Receptacle/Socket Type #2</b>	U-Lock IEC C19
- Quantity on Face	6
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100-120V or 208-240V
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	72in / 1829mm Vertical Rackmount
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	61.25in and 64.75in / 1556mm and 1645mm
<b>Product Warranty</b>	5-year limited warranty
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	UL & c-UL Listed 62368-1
<b>Certification/Agency Approvals</b>	UKCA Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	RCM Mark (EMC Only)
<b>Certification/Agency Approvals</b>	FCC Part 15 Class A Conformance
<b>Certification/Agency Approvals</b>	China RoHS
<b>Certification/Agency Approvals</b>	C <sub>ρ</sub> Mark
<b>Chassis Dimensions (LxWxD)</b>	72in x 2in x 2in / 1829mm x 51mm x 51mm
<b>Shipped Weight</b>	16lbs (7.26kg)