

OVERVIEW

Rack Transfer Switch (RTS) delivers redundant power to single corded devices. The RTS automatically detects the loss of power and switches the power load (no phase-synchronization required) to the alternative power source in less than 4-8 milliseconds without the need for human intervention.

Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



Part #: VA1G9100

Model Number: AG01X1R1-12CF13-3PS6PS6B211-D

Category: Rack Transfer Switch

Sub Category: Basic Upgradeable

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU, Rack Transfer Switch Basic Upgradeable, 32A, 230V, 7.3kW, Horizontal, (12) Combination C13/C19, 10ft / 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Monitoring:

No Monitoring (Upgradeable with IMD module)

Plug Form:



1P+N+E (IP44)

Receptacle:



Combination C13/C19
(Quantity: 12)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring	No Monitoring (Upgradeable with IMD module)
Power Switching	Auto Switching - In Event of Power Failure
Transfer Time	<4-8ms
Out of Phase Transfers	Yes
Front Panel HMI LED Overlay	Yes
Quantity Of Inputs	2 (Dual Input)
Voltage	200-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz
Over Current Protection	(2) 16A Single Pole Magnetic Breakers (10kAIC Rated)
Switch	Breaker/Switch Combination
Scrolling / Rotatable Digital Display	Yes
Power Cable Wire Gauge	4mmÂ² H07RN-F
Power Cable Length	10ft / 3m
Power Entry Location	Left Rear
Plug Type	(2) IEC60309 1P + N + E, 32A, 250V Connector, Splashproof IP44
Receptacle/Socket Type #1	Combination C13/C19
- Quantity on Rear	12
- Quantity per Breaker	6
- Circuit Color ID	2 Circuit = Orange, Green
- Style	Banks of 6
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Adjustable 4 Post Mounting (Range)	Yes (24" - 37")
2 Post Mounting Kit	Yes
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	C _P Mark
Chassis Dimensions (HxWxD)	1.72in x 17in x 18in / 44mm x 432mm x 457mm
Shipped Weight	16lbs (7.26kg)

