

OVERVIEW

Rack Transfer Switch (RTS) delivers redundant power to single corded devices. The RTS automatically detects the loss of power and switches the power load (no phase-synchronization required) to the alternative power source in less than 4-8 milliseconds without the need for human intervention.

Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote outlet-level power monitoring options offer quick access to critical power usage information down to the device level to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices.



Part #: VA7N31A0

Model Number: ANU5M1R6-06CF18-3TL6TL6A011-D

Category: Rack Transfer Switch

Sub Category: Switched Outlet Level Monitoring

Power Configuration: 30A, 208V, 4.9kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU, Rack Transfer Switch Switched Outlet Level Monitoring, 30A, 208V, 4.9kW, Horizontal, (6) Combination C13/C19, 10ft / 3m power cords with L6-30P, Black Powder Coat.

Monitoring:

Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.

Plug Form:



L6-30P

Receptacle:



Combination C13/C19
(Quantity: 6)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|---|---|
| Monitoring | Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display. |
| Input Monitoring | Phase (A) Monitoring (kWh, W, VA, PF, V, A) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements |
| Circuit Monitoring | Circuit / Breaker Monitoring (A) Circuit/Breaker Current Measurements Independently Tested and Verified at 1% Accuracy |
| Outlet Monitoring | Outlet Monitoring (kWh, W, VA, PF, V, A) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements. |
| Remote Power Management | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up |
| Power Switching | Auto Switching - In Event of Power Failure |
| Transfer Time | <4-8ms |
| Out of Phase Transfers | Yes |
| Front Panel HMI LED Overlay | Yes |
| Rear Panel LED Overlay | Yes |
| Quantity Of Inputs | 2 (Dual Input) |
| Voltage | 200-240V |
| Current | 30A |
| VA per Input (Load Capacity) | 4.9kW (208V) |
| Frequency | 50/60Hz |
| Over Current Protection | (2) 20A Double Pole Magnetic Breakers (10kAIC Rated) |
| Switch | Breaker/Switch Combination |
| LCD Touchscreen Display / Auto Oriented | Yes |
| Indicators - LED(s) | 6 |
| Power Cable Wire Gauge | 10/3 |
| Power Cable Length | 10ft / 3m |
| Power Entry Location | Left Rear |
| Plug Type | (2) NEMA L6-30P Twistlock |
| Receptacle/Socket Type #1 | Combination C13/C19 |
| - Quantity on Rear | 6 |
| - Quantity per Breaker | Breaker 1 = 4, Breaker 2 = 2 |
| - Circuit Color ID | 2 Circuit = Orange, Green |
| - Style | Banks of 6 |
| - Voltage per Receptacle/Socket | 208V |

| | |
|------------------------------------|--|
| Network Connection | Dual 10/100/1000Mbps Ethernet |
| Protocols Supported | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP |
| Data Access Formats | CSV datalog, JSON API, JSON datalog |
| USB Support | Yes |
| IP Reset Button | Yes |
| Hard Reboot Button | Yes |
| Serial Connection | RS232 via RJ45 |
| Remote Sensor RJ Connection Jacks | 1 (Supports up to 16 Sensors) |
| Maximum Operating Temperature | 60C / 140F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 19in / 483mm Horizontal Rackmount |
| Adjustable 4 Post Mounting (Range) | Yes (24" - 37") |
| 2 Post Mounting Kit | Yes |
| Product Warranty | 5-year limited warranty |
| Certification/Agency Approvals | UL & c-UL Listed 62368-1 |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | FCC Part 15 Class A Conformance |
| Chassis Dimensions (HxWxD) | 1.72in x 17in x 18in / 44mm x 432mm x 457mm |
| Shipped Weight | 12lbs (5.44kg) |