

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.

## Part #: VP0G0101

**Model Number:** MG00X7R0-08SKZ3-1C14A6H10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 10A, 230V, 2.3kW

**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Standard, 10A, 230V, 2.3kW, Horizontal, (8) German Schuko, 3m power cord with C14, Black Powder Coat.

### Plug Form:



C14

### Receptacle:



German Schuko  
(Quantity: 8)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V
Current	10A
VA per Input (Load Capacity)	2.3kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	1.0mm <sup>2</sup> H05VVF

Power Cable Length	3m
Plug Type	IEC60320 C14 (corded)
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	8
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Flush Mount	Yes
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Chassis Dimensions (HxWxD)	67mm x 435mm x 60mm
Shipped Weight	4lbs (1.81kg)