

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.

Part #: VPOG8004

Model Number: MG00XEBO-20SKZ3-2PS6B2A10-S

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary:

rPDU, Basic Standard, 16A, 230V, 3.6kW, Vertical, (20) German Schuko, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Plug Form:



1P+N+E (IP44)

Receptacle:



German Schuko
(Quantity: 20)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60Hz
Over Current Protection	None
Switch	No
Power Cable Wire Gauge	2.5mm ² H07RN-F

Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 16A, 250V, Splashproof IP44
Receptacle/Socket Type #1	German Schuko
- Quantity on Face	20
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	66in / 1683mm Vertical Rackmount
GE Vertical Mounting Bracket	Yes
Toolless Mounting Hardware - Center to Center Spacing	1556mm and 1645mm
Product Warranty	5-year limited warranty
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	UKCA Marked
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	Complies with EN 55032 and EN 55035
Certification/Agency Approvals	RoHS Compliant
Chassis Dimensions (LxWxD)	1683mm x 54mm x 50mm
Shipped Weight	14lbs (6.35kg)