

## OVERVIEW

Upgradeable Switched Unit Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of input power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. Upgrade the hot-swappable monitoring device on select units to leverage new technologies and accommodate changing business needs.

### Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce



## Part #: VP5N21A1

**Model Number:** MNS5M1R5-12S203-2TL5A0H10-S

**Category:** Switched

**Sub Category:** Unit Level Monitoring

**Power Configuration:** 20A, 120V, 1.9kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Switched Unit Level Monitoring EC, 20A, 120V, 1.9kW, Horizontal, (12) NEMA 5-20R, 10ft / 3m power cord with L5-20P, Black Powder Coat.

### Monitoring:

Input power monitoring with Outlet switching. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.

### Plug Form:



L5-20P

### Receptacle:



NEMA 5-20R  
(Quantity: 12)

### Chassis Color Options:



deployment time with self-configuration of downstream devices.

To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

|                                         |                                                                                                                                                                       |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Monitoring                              | Input power monitoring with Outlet switching. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display. |
| Input Monitoring                        | Phase (A) Monitoring (kWh, W, VA, PF, V, A)                                                                                                                           |
|                                         | Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements                                                                       |
| Remote Power Management                 | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up                                                                            |
| Quantity Of Inputs                      | 1                                                                                                                                                                     |
| Voltage                                 | 100-120V                                                                                                                                                              |
| Current                                 | 20A                                                                                                                                                                   |
| VA per Input (Load Capacity)            | 1.9kW (120V)                                                                                                                                                          |
| Frequency                               | 50/60Hz                                                                                                                                                               |
| Over Current Protection                 | None                                                                                                                                                                  |
| Switch                                  | No                                                                                                                                                                    |
| LCD Touchscreen Display / Auto Oriented | Yes                                                                                                                                                                   |
| Indicators - LED(s)                     | 12                                                                                                                                                                    |
| Power Cable Wire Gauge                  | 12/3                                                                                                                                                                  |
| Power Cable Length                      | 10ft / 3m                                                                                                                                                             |
| Power Entry Location                    | Rear                                                                                                                                                                  |
| Plug Type                               | NEMA L5-20P Twistlock                                                                                                                                                 |
| Receptacle/Socket Type #1               | NEMA 5-20R                                                                                                                                                            |
| - Quantity on Rear                      | 12                                                                                                                                                                    |
| - Style                                 | Individual                                                                                                                                                            |
| - Voltage per Receptacle/Socket         | 120V                                                                                                                                                                  |
| Network Connection                      | Dual 10/100/1000Mbps Ethernet                                                                                                                                         |
| Protocols Supported                     | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP                                                      |
| Data Access Formats                     | CSV datalog, JSON API, JSON datalog                                                                                                                                   |
| USB Support                             | Yes                                                                                                                                                                   |
| IP Reset Button                         | Yes                                                                                                                                                                   |
| Hard Reboot Button                      | Yes                                                                                                                                                                   |
| Serial Connection                       | RS232 via RJ45                                                                                                                                                        |
| Remote Sensor RJ Connection Jacks       | 1 (Supports up to 16 Sensors)                                                                                                                                         |
| Maximum Operating Temperature           | 60C / 140F                                                                                                                                                            |
| Heavy Steel - Powder Coat Finish        | Black                                                                                                                                                                 |
| Configuration                           | 19in / 483mm Horizontal Rackmount                                                                                                                                     |
| Adjustable Mount Brackets               | Yes                                                                                                                                                                   |
| Country of Origin                       | USA, TAA Compliant and Buy American Act COTS Compliant                                                                                                                |
| Product Warranty                        | 5-year limited warranty                                                                                                                                               |

|                                |                                             |
|--------------------------------|---------------------------------------------|
| Certification/Agency Approvals | UL & c-UL Listed 62368-1                    |
| Certification/Agency Approvals | RoHS Compliant                              |
| Certification/Agency Approvals | FCC Part 15 Class A Conformance             |
| Chassis Dimensions (HxWxD)     | 1.72in x 17in x 12in / 44mm x 432mm x 305mm |
| Shipped Weight                 | 10lbs (4.54kg)                              |