

# **OVERVIEW**

Upgradeable Switched Unit Level
Monitored rPDUs provide reliable power
distribution to critical IT equipment
while delivering individual outlet level
control and a comprehensive view of
input power usage via remote network
access. Includes environmental
monitoring capabilities to obtain realtime environmental metrics. Upgrade the
hot-swappable monitoring device on
select units to leverage new
technologies and accommodate
changing business needs.

#### **Benefits**

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce



## Part #: VP5U20A3

Model Number: MUS5MGM0-12P027-2C20A9A00-S

Category: Switched

Sub Category: Unit Level Monitoring

Power Configuration: 16A OR 20A, 120V OR 208V OR 230V, 1.9kW or 3.3kW or 3.6kW

Physical Configuration: 34in / 864mm, Vertical

Product Summary: rPDU, Switched Unit Level Monitoring EC, 16A OR 20A, 120V OR 208V OR 230V, 1.9kW

or 3.3kW or 3.6kW, Vertical, (10) Locking IEC C13, (2) Locking IEC C19, C20, Black

Powder Coat.

Monitoring: Input power monitoring with Outlet switching. Environmental monitoring via optional

remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.

#### Plug Form: Receptacle:








Locking IEC C13 (Quantity: 10)

Locking IEC C19 (Quantity: 2)

#### **Chassis Color Options:**



To discuss color options, contact your local sales representative.

### **Product Specification and Options**

#### **System Features**

deployment time with selfconfiguration of downstream devices.

Monitoring	Input power monitoring with Outlet switching. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.
Input Monitoring	Phase (A) Monitoring (kWh, W, VA, PF, V, A)
	Power Measurements Compliant with ANSI C12.1 and IEC 62053- 21 at 1% Accuracy Class Requirements
Remote Power Management	Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up
Quantity Of Inputs	1
Voltage	100-240V
Current	16A or 20A
VA per Input (Load Capacity)	1.9kW (120V), 3.3kW (208V), 3.6kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Switch	No
LCD Touchscreen Display / Auto Oriented	Yes
Indicators - LED(s)	12
Power Entry Location	Bottom Front
Plug Type	IEC60320 C20 Power Inlet (cord sold separately)
Combined Total Receptacle/Socket Quantity	12
Receptacle/Socket Type #1	U-Lock IEC C13
- Quantity on Face	10
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100-240V
Receptacle/Socket Type #2	U-Lock IEC C19
- Quantity on Face	2
- U-Lock Color ID	1 Circuit = Orange
- Style	Individual
- Voltage per Receptacle/Socket	100-240V
Network Connection	Dual 10/100/1000Mbps Ethernet
Protocols Supported	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP
Data Access Formats	CSV datalog, JSON API, JSON datalog
USB Support	Yes
IP Reset Button	Yes
Hard Reboot Button	Yes
Serial Connection	RS232 via RJ45
Remote Sensor RJ Connection Jacks	1 (Supports up to 16 Sensors)
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U
7938 Vertical Mounting Bracket Kit	Yes
7000 FOLGOGI MOGILLING DIGCROL RIL	

622mm
5-year limited warranty
CE Marked
UL & c-UL Listed 62368-1
UKCA Marked
Complies with IEC 62368-1 (DOC Available)
Complies with EN 55032 and EN 55035
RoHS Compliant
RCM Mark (EMC Only)
FCC Part 15 Class A Conformance
China RoHS
C <sub>P</sub> Mark
34in x 2in x 2.6in / 864mm x 51mm x 66mm
1.4in / 36mm
18lbs (8.16kg)